

## TDS OF POLY ACRYL 117(II)

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### Product information

**Trade name** : POLY ACRYL 117(II)

**Company** : No:771,zereshki alley tajbakhsh street , 25 km karaj special road  
,Tehran-Iran

**Telephone** : (+98 263) 6102231-2 , (+98 263) 6102299

**Telefax** : (+98 263) 6102023

**Email address** : [info@awachimie.com](mailto:info@awachimie.com)

**Use of the Substance** : **PA 117 (II)** is an water based glue/adhesive designed for the production of adhesive products and other pressure sensitive materials.

---

#### - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Colour	milky
Odour	faint

Total solid (ASTM D 2369)	45±1%
Viscosity (23°C, Brookfield RV #5/RPM 10)	70-150p
pH (ASTM D 1293)	7-8
MFFT (ISO 2811)	+2°C
Density (ASTM D1475 )	1/04-1/1g/cm <sup>3</sup>
Water solubility	dilutable

#### - FIRST AID MEASURES

##### General advice

Remove contaminated or saturated clothing.

##### Skin contact

Wash off with plenty of water and soap immediately.

##### Eye contact

Rinse with plenty of water immediately, seek medical advice if necessary.

##### Ingestion.

Seek medical advice.

## **- HANDLING AND STORAGE**

### **Handling**

#### **Safe handling advice**

Avoid contact with skin and eyes.

Application, processing: Provide good ventilation or extraction.

#### **Advice on protection against fire and explosion**

Normal measures for preventive fire protection.

### **Storage**

#### **Requirements for storage areas and containers**

Keep container tightly closed.

Protect from frost.

## **- OTHER INFORMATION**

NOTICE: Awa shimi believes the information contained here is accurate. However, Awa shimi chimie makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained by the use thereof. , Awa shimi assumes no responsibility for injury from the use of the product described herein.